

NO THROUGH ROAD/NO DIVERSION ROUTE AVAILABLE

USRN: 47302987



ROAD CLOSURE :

NOTES

- 1 All traffic signs shall comply with Chapter 8 of the Traffic Signs Manual
- 2 All traffic management equipment shall be provided by the Contractor, unless otherwise specified.
- 3 All signs shall be positioned so as not to be obscured by any other objects and shall not obstruct any other sign, permanent or temporary as much as is reasonably practicable.
- 4 All traffic signs shall meet the reflectorisation requirements of BS 873 : Part 6 : 1983, Table 1.
- 5 Works Access/Egress to be positioned to suit ongoing works.

NOTES

- 1 All traffic signs shall comply with Chapter 8 of the Traffic Signs Manual
- 2 Maximum distance between any two temporary traffic signals to be 240m. Minimum distance between any two temporary traffic signals to be 30m.
- 3 Temporary traffic signals shall not occur within 150m of an existing level crossing. Pelican crossing or signalised junction without the consent of the Engineer. The Engineer shall consult with the authority responsible for any of these types of facility prior to traffic management being installed in adjacent areas.
- 4 Coning shall be installed at 45° to the edge of carriageway, as generally indicated.

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 2) 45° tapers have 1.5m spacing, no relaxations.
- 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

KEY

- Cone
- Works Area
- Safety zone
- Sign
- Diversion Route
- Pedestrian Route
- Pedestrian Barriers
- TEMPORARY PEDESTRIAN CROSSING

Flordd yma ar gau o'r
-- / -- / -- / -- / --
This road will be closed
-- / -- / -- / -- / --
Advance warning signs to be installed prior to installation of closure.

Client

openreach

MYNDEFA
WAITH
WORKS
ACCESS

ALLANFA
WAITH
WORKS
EXIT

Works access/ works exit to be risk assessed on site for suitability of location

Address

Magor with Undy,
Undy, Monmouthshire,
Wales
NP26 3NR

TM Type

ROAD CLOSURE

MJ Quinn

Design: M.CARR Drawn: M.CARR Chkd:P.MATHER
Date: 17/07/20 Date: 17/07/20 Date: 17/07/20
Scale: NTS Status: DRAFT

Drawing No
MJQ2020-1735 - WBLG43T - MAGOR - RCD

Rev: